

MEDICAL GRADE ISOLATION POWER TRANSFORMER

MD-250-E

Electrical Specifications (@25C)

- 1. Maximum Power: 250VA
- 2. Input Voltage (power cord): 240VAC±10%, 50/60Hz
- 3. Output Voltage (receptacle): 120.0VAC @ 2.08Max1
- 4. Voltage Regulation: 8% TYP from full load to no load
- 5. Hipot:

Input to output: 3000VAC

Input and output to enclosure (Ground): 1500VAC

- 6. Efficiency: 92% TYP. @ full load
- 7. Operating ambient temperature: Not to exceed 60°C
- 8. Leakage current: less than 50uA; typical 10uA
- 9. Fusing: Replace only with 1.8, 250VAC, slow blo, UL listed fuses. Recommended Cooper Bussman MDL1-8/10-R.



These medical grade isolation boxes are built using a toroidal transformer construction that inherently helps reduce stray fields, increases efficiency and minimizes size compared to traditional EI transformers. Built with Class F (155°) insulation system. The enclosure is made of steel and powder coated white.

Medical isolation transformer box is certified to UL 60601-1, 2nd edition medical standard and CSA-C22.2.No. 601.1M90, 2005

UL: (E352717), UL60601-1, 2nd edition & CAN/CSA-C22.2 No. 601.1M90, 2005

UL: (E514503), AAMI/IEC 60601-1:2005 + AMD 1:2012 & CSA CAN/CSA-C22.2 NO. 60601-1:14

Note: Not for use in life critical application




Mounting:


Rubber feet for horizontal mounting.

Connections:

Input: 11ft medical grade power cord with Nema 6-15P plug.

Output: Duplex receptacle. Nema 5-15R.





155C

Please refer to instruction manual for safety precautions.


RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.


* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757

460 Harley Knox Blvd. Perris, California 92571







Dimensions: mm Weight: 4.0Kg

Warranty: 5 years

Release Date: August 22, 2025

¹ Combined loads connected to receptacle(s) must not exceed maximum current rating.